

# **RESIBLOCK TRADE**

## **APPLICATION GUIDE SUMMARY\***

### **Surface Preparation:**

Surfaces to be treated must be dry, free from grease, oil, debris and previous sealers. Joints should be filled or topped up to the bottom of the chamfer with clean, **dry**, compacted sand of the correct specification.

### **Coverage:**

Concrete & Clay Block Paving 1.8—2.2m<sup>2</sup> per litre.

Flag Paving 2.2—4m<sup>2</sup>. If in doubt contact Resiblock Technical on 01268 273344.

### **Application:**

By brush, roller, spray or squeegee (STIR WELL BEFORE USE) generally the paver type will dictate the most appropriate application tool. Ensure sand filled joints are fully flooded with RESIBLOCK TRADE. Work the product into the joints for maximum penetration. Ensure the surface is evenly coated.

PLEASE NOTE: The product must **not** be allowed to pond within the depressions of riven surfaces, remove with builders sponge/dry roller.

Clean accidental spills and splashes immediately with a clean damp cloth.

### **Curing:**

Curing commences immediately, to leave surface dry after approximately 4-8 hours (depending on weather conditions).

### **Appearance:**

RESIBLOCK TRADE contains micronised particles that produce an opaque appearance when wet but will be clear when dry. We recommend the application of a trial area where the appearance of the treated surface is of particular importance and to test that the paving is sufficiently porous to absorb the solution evenly and without leaving a surface film.

### **Safety:**

Do not use in the presence of foodstuffs. Wear personal protective clothing, goggles and gloves.

### **Storage:**

Store at a temperature range of 5°C—30°C. Protect from frost. Do not allow the product to freeze.

### **Shelf Life:**

18 months in Resiblock Ltd's unopened container.

### **Transport:**

Not classified as hazardous for road transportation.

## **WARNING**

If you have not used RESIBLOCK TRADE before, it is recommended that you telephone the number given below so that full application information can be sent to you, free of charge. Failure to read and understand this information may result in unacceptable sealer performance both technically and aesthetically.

RESIBLOCK TRADE cannot be used on any previously sealed surfaces. For further advice on previously sealed surfaces contact RESIBLOCK's Technical Dept.

**FOR FREE ADVICE TELEPHONE  
RESIBLOCK  
01268 273344**

\* ***This fact sheet is not intended to replace the full application instructions, which must be read prior to application.***

Whilst Resiblock Limited believe that the data contained herein is factual, the opinions expressed are those of experts (qualified or otherwise) regarding the results of tests. The data is not to be taken as a warranty or representation for which Resiblock Limited assumes legal responsibility. This data is offered solely for your consideration, investigation and verification. Any use of this data must be determined by the user to be according to the applicable laws and regulations

Resiblock Limited try to ensure any advice, recommendations or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our products are used, hence our advice does not release **end-users from the obligation to satisfy themselves by prior testing that the product/s is suitable for their specific application, and that the actual conditions of use are suitable.**

Accordingly no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors. Each end-user should always ensure that they have consulted our latest publications and that the relevant information concerning this material is communicated to all members of their organisation handling our products.

Resiblock Limited's liability is for replacement of material proved to be defective only. Products are sold subject to our Standard Conditions of Sale.

The Company's policy of continuous product development and improvement renders specifications liable to modifications. Information provided in this literature is therefore subject to change without prior notification.

This entire document is copyright protected. All rights reserved. First published in Great Britain. No part of this publication may be produced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording and/or otherwise without prior written permission of the publishers.

© Resiblock Limited 1993