

Soil and Mechanical Vent Adaptors & Flexipipes



Packs consist of an adaptor, together with Klobber's quick push-fit high quality flexible pipe.

Product features & benefits

- Quick and simple connection to internal pipework
- Lightweight, durable – no tile cutting or lead flashing required
- Pressure tested to comply with relevant British Standards

Area of application

- Suitable for roofs with a pitch over 17.5°

Material / Colour

Adaptor - Rigid PVC, 10K Slate Vent Adaptor – polypropylene
Flexipipe - Galvanised spring steel wire helix encapsulated in double-ply PVC wall

Colour

Adaptors & Flexipipes Black

Product Code / Dimensions

1. & 6.

Adaptor and Flexipipe (Universal/Large Slate Vents) KG979800
170mm long x 120mm wide x 90mm deep – 105mm internal diameter

2. & 6.

Adaptor and Flexipipe (10K Slate Vent/Profile-Line® Vents) KG979200
76mm long x 86mm wide x 120mm deep – 105mm internal diameter

3. & 6.

Adaptor and Flexipipe (Uni-Plain Tile Vent) KG992800
273mm long x 44mm wide x 200mm deep – 105mm internal diameter

2.

Adaptor (10K Slate Vent/Profile-Line® Vents) KG979100
76mm long x 86mm wide x 120mm deep – 105mm internal diameter

3.

Adaptor (Plain Tile Vent) KG990500
273mm long x 44mm wide x 200mm deep – 105mm internal diameter

4.

Adaptor (Clay Plain Tile Vent) KG8003

Adaptor for High Flow Vents for Bold Roll,
Stonewold Mark II, Regent, Wessex (not shown) KG8000

1.

Adaptor (100mm Universal Vent Tile) KG968300

Adaptor (125mm Universal Vent Tile - not shown) KG979000

Flexipipe (75/100mm - not shown) KG972400

6.

Flexipipe (100/100mm) KG979900

5.

Flexipipe (100/125mm) KE8047

Installation

Universal Vent Tile/Large Slate/10K Slate Vent/Profile-Line® Vent Tile/Uni-Plain Tile Vent

Adaptor is clipped onto the downpipe of the Universal Vent Tile, Profile-Line® Vent Tile, Slate Vent or 10K Slate Vent ideally before installation. Flexipipe is secured to adaptor with a unique push fit connector. Full fixing instructions are provided with the product.

Uni-Flexipipes - 75/100mm & 100/100mm

The 75/100mm Flexipipe is secured to the integral downpipe of the Small Slate Vent with stainless steel clip and a second clip is used to connect it to internal pipework. The 100/100mm is secured to the adaptor or downpipe with a unique push fit connector. Full fixing instructions are supplied with each product.

Regulations and certifications

Pressure tested to comply with relevant Building Regulations and British Standards.

TS-00#19-UK-0314. We assume no liability for typing errors.

Klobber Ltd

Unit 6F · East Midlands Distribution Centre · Short Lane · Castle Donington · Derbyshire · DE74 2HA
Tel. +44 (0)1332 813 050 · Fax +44 (0)1332 814 033 · info@klobber.co.uk · www.klobber.co.uk

KLOBBER